



## Stocked Compression Coil Springs

| Part Number | O.D. (in.) | Length | Wire Dia. (in.) | Solid Height | Maximum Safe Load | Quantity per 1 Package |
|-------------|------------|--------|-----------------|--------------|-------------------|------------------------|
| C-500       | 0.1562     | 0.5625 | 0.023           | 0.276        | 5.300             | 6                      |
| C-510       | 0.250      | 0.500  | 0.035           | 0.262        | 11.400            | 6                      |
| C-516       | 0.156      | 1.000  | 0.011           | 0.138        | 0.620             | 6                      |
| C-520       | 0.1875     | 0.875  | 0.016           | 0.272        | 0.810             | 6                      |
| C-526       | 0.1875     | 1.000  | 0.028           | 0.483        | 7.860             | 6                      |
| C-530       | 0.2187     | 1.000  | 0.020           | 0.235        | 2.600             | 6                      |
| C-532       | 0.1875     | 1.000  | 0.013           | 0.140        | 0.850             | 6                      |
| C-550       | 0.1875     | 1.000  | 0.016           | 0.200        | 1.570             | 6                      |
| C-554       | 0.250      | 1.000  | 0.020           | 0.195        | 2.290             | 6                      |
| C-556       | 0.3125     | 0.625  | 0.026           | 0.181        | 3.020             | 6                      |
| C-562       | 0.250      | 1.000  | 0.035           | 0.464        | 11.400            | 6                      |
| C-566       | 0.375      | 0.750  | 0.032           | 0.230        | 4.470             | 6                      |
| C-570       | 0.125      | 1.375  | 0.014           | 0.399        | 1.560             | 6                      |
| C-576       | 0.1562     | 1.375  | 0.016           | 0.348        | 1.870             | 6                      |
| C-578       | 0.1875     | 1.375  | 0.013           | 0.179        | 0.850             | 6                      |
| C-580       | 0.1875     | 1.375  | 0.028           | 0.652        | 7.860             | 6                      |
| C-582       | 0.1875     | 1.375  | 0.016           | 0.260        | 1.570             | 6                      |
| C-600       | 0.2187     | 1.375  | 0.020           | 0.305        | 2.600             | 4                      |
| C-604       | 0.2187     | 1.375  | 0.023           | 0.385        | 3.890             | 4                      |
| C-608       | 0.250      | 1.375  | 0.020           | 0.250        | 2.290             | 4                      |
| C-612       | 0.2812     | 1.375  | 0.028           | 0.444        | 4.420             | 4                      |
| C-614       | 0.3125     | 1.250  | .041            | .615         | 10.60             | 4                      |
| C-624       | 0.375      | 1.125  | 0.041           | 0.461        | 9.000             | 4                      |
| C-632       | 0.4375     | 1.0625 | 0.041           | 0.359        | 7.770             | 4                      |
| C-650       | 0.2187     | 1.750  | 0.013           | 0.375        | 2.600             | 4                      |
| C-652       | 0.2187     | 1.375  | 0.028           | 0.526        | 6.840             | 4                      |
| C-660       | 0.3125     | 1.750  | 0.016           | 0.156        | 0.840             | 4                      |
| C-664       | 0.3437     | 1.500  | 0.047           | 0.796        | 14.400            | 4                      |
| C-668       | 0.375      | 1.500  | 0.026           | 0.271        | 2.530             | 4                      |
| C-672       | 0.375      | 1.750  | 0.035           | 0.505        | 5.750             | 4                      |
| C-676       | 0.4375     | 2.125  | 0.032           | 0.402        | 3.850             | 4                      |
| C-680       | 0.3125     | 2.000  | 0.047           | 1.150        | 15.700            | 4                      |
| C-690       | 0.4375     | 2.250  | 0.041           | 0.670        | 7.700             | 2                      |



## Stocked Compression Coil Springs

| Part Number | O.D. (in.) | Length | Wire Dia. (in.) | Solid Height | Maximum Safe Load | Quantity per 1 Package |
|-------------|------------|--------|-----------------|--------------|-------------------|------------------------|
| C-692       | 0.625      | 1.500  | 0.041           | 0.301        | 5.520             | 2                      |
| C-700       | 0.500      | 1.000  | 0.062           | 0.542        | 21.400            | 2                      |
| C-702       | 0.5625     | 1.000  | 0.054           | 0.396        | 12.900            | 2                      |
| C-704       | 0.500      | 1.500  | 0.041           | 0.400        | 6.840             | 2                      |
| C-706       | 0.5625     | 1.375  | 0.072           | 0.738        | 28.200            | 2                      |
| C-712       | 0.6875     | 1.250  | 0.092           | 0.755        | 44.700            | 2                      |
| C-714       | 0.375      | 2.250  | 0.062           | 1.458        | 27.700            | 2                      |
| C-720       | 0.500      | 1.750  | 0.062           | 0.859        | 21.400            | 2                      |
| C-724       | 0.4375     | 2.000  | 0.054           | 0.932        | 16.300            | 2                      |
| C-730       | 0.4062     | 2.750  | 0.047           | 1.280        | 12.400            | 2                      |
| C-736       | 0.500      | 2.750  | 0.072           | 1.560        | 31.300            | 2                      |
| C-740       | 0.625      | 2.500  | 0.080           | 1.140        | 44.200            | 2                      |
| C-742       | 0.625      | 2.750  | 0.054           | 0.770        | 11.700            | 2                      |
| C-750       | 0.750      | 2.000  | 0.080           | 0.860        | 28.700            | 2                      |
| C-752       | 0.938      | 2.000  | 0.080           | 0.667        | 23.200            | 2                      |
| C-756       | 0.719      | 3.500  | 0.041           | 0.461        | 4.820             | 2                      |
| C-766       | 0.563      | 3.000  | 0.054           | 0.954        | 12.900            | 2                      |
| C-782       | 0.625      | 3.000  | 0.080           | 1.340        | 44.200            | 2                      |
| C-792       | 0.875      | 3.000  | 0.105           | 1.503        | 52.700            | 2                      |
| C-802       | 1.375      | 4.375  | 0.148           | 1.977        | 87.400            | 1                      |
| C-806       | 1.500      | 3.500  | 0.148           | 1.600        | 67.000            | 1                      |
| C-810       | 1.375      | 2.750  | 0.120           | 1.500        | 40.000            | 1                      |
| C-814       | 1.375      | 2.500  | 0.135           | 1.114        | 67.600            | 1                      |
| C-818       | 1.125      | 4.000  | 0.120           | 1.727        | 59.600            | 1                      |
| C-822       | 0.938      | 4.000  | 0.148           | 2.632        | 124.000           | 2                      |
| C-826       | 1.000      | 3.500  | 0.120           | 1.171        | 66.500            | 2                      |
| C-830       | 1.125      | 3.000  | 0.105           | 1.108        | 41.600            | 2                      |
| C-832       | 1.000      | 3.000  | 0.120           | 1.536        | 66.600            | 2                      |
| C-834       | 1.188      | 22.75  | 0.120           | 1.205        | 56.600            | 2                      |
| C-836       | 0.875      | 4.000  | 0.080           | 1.280        | 24.800            | 2                      |
| C-838       | 0.750      | 3.500  | 0.080           | 1.380        | 28.700            | 2                      |
| C-850       | 0.625      | 5.000  | 0.091           | 2.900        | 48.700            | 2                      |
| C-856       | 0.750      | 6.000  | 0.091           | 2.790        | 41.300            | 2                      |



## Stocked Compression Coil Springs

| Part Number  | O.D. (in.) | Length | Wire Dia. (in.) | Solid Height | Maximum Safe Load | Quantity per 1 Package |
|--------------|------------|--------|-----------------|--------------|-------------------|------------------------|
| <b>C-858</b> | 0.688      | 6.000  | 0.072           | 2.160        | 23.400            | 2                      |
| <b>C-864</b> | 0.875      | 6.000  | 0.091           | 2.280        | 35.700            | 1                      |
| <b>C-874</b> | 1.375      | 6.000  | 0.120           | 1.680        | 50.000            | 1                      |
| <b>C-878</b> | 0.625      | 9.000  | 0.080           | 3.720        | 44.200            | 1                      |
| <b>C-892</b> | 1.125      | 7.000  | 0.162           | 4.150        | 134.000           | 1                      |